



Del Sol LX

LX Desktop Series

Programming

Our Del Sol LX advanced firmware command language, CPL, is so easy to use, programming it into any application is a snap.

Upgrading

The use of flashable memory allows for easy firmware upgrades to get you the latest features available for your printer.

Capacity

You don't have to deal with memory capacity issues with the Del Sol LX, with 4MB of flash memory in every printer, you have plenty of room to add custom fonts, graphics, and custom programming.

Size

You don't have to pay the big bucks for the big box to get performance. You want a performing product that doesn't empty your bankroll, think Del Sol LX.

Economic

The affordable pricing of the Del Sol LX allows you to replace that big box printer at a fraction of the cost. Start saving now with the Del Sol LX.

Large Roll Capacity

Spend less time swapping media and more time printing labels with Del Sol's massive 7" O.D. user configurable option. Measuring in at over 6,000 inches long, this is the largest roll in its class.

Serviceability

Quickly replace the printhead and platen without removing the printer from service.

Maxatec
barcode printers



Cognitive
SOLUTIONS INC.

www.maxatec-europe.com

| LDx24-2043-xxx | |
|--------------------------------|---|
| Printing | |
| Technology | Direct Thermal/Thermal Transfer |
| Maximum Width | 53mm (2.2") |
| Maximum Length | 4064mm at 101dpi, 1016 at 203dpi |
| Maximum Speed | 3" Per Second (76mm Per Second) |
| Resolution | Selectable 101 or 203 dpi |
| Media | |
| Roll Width | 19mm - 61mm (0.75" - 2.4") |
| Roll Diameter | 127mm (5") user configurable upto 203mm (7") |
| Ribbon Length | 140m (5500") |
| Indexing | Black bar, notch and gap |
| Supported Bar Codes | UPC, EAN, EAN128, Code39, Plessey, MSI/MSI1, Code 16k, Code128, Codabar, MaxiCode, PDF 417, Code93, I2 of 5, more |
| Fonts | |
| Bitmapped | 7 styles with upto 10x10 magnification, variable boldness and spacing (all models) |
| AGFA Fonts | Sans-serif font in 7pt, upto 4x4 magnification, variable boldness and spacing (all models) |
| Scalable Smooth Fonts | 3 ultra font styles for smooth characters any size and boldness (all models) |
| Rotations | 360° in 90° increments |
| Graphics | |
| Features | Foreground and background bitmapped graphics, sizeable graphics window (all models) |
| Format | PCX, BMP |
| Memory | |
| RAM | 2MB |
| Flash | 512KB Flash, +2MB and 4MB options (all models) |
| Communications | |
| Standard | Serial and parallel |
| Optional | Internal Ethernet |
| Electrical | 100, 115, or 230 VAC, 50/60Hz |
| Environmental | |
| Operating | 41°F to 104°F (5°C to 40°C) |
| Storage | -4°F to 122°F (-20°C to 50°C) 25-85% non condensing RH |
| Dimensions H x W x D | 177.8mm x 114.3mm x 254mm 7" x 4.5" x 10" |
| Weight | 3.1lb (1.41kg) |
| Accessories | |
| Supplied | Quick Start Guide, power supply, CD including: Windows® drivers, programmers guide, label design software |
| Optional | Ethernet connectivity, communications cables, annual service contracts, cutter, dispenser, real time clock |
| Printhead Life | 2 Million" (50km) |

| LDx42-2043-xxx | |
|--------------------------------|---|
| Printing | |
| Technology | Direct Thermal/Thermal Transfer |
| Maximum Width | 104mm (4.1") |
| Maximum Length | 2032mm at 101dpi, 513mm at 203dpi |
| Maximum Speed | 3" Per Second (76mm Per Second) |
| Resolution | Selectable 101 or 203 dpi (300dpi optional) |
| Media | |
| Roll Width | 25.4mm - 108mm (1" - 4.25") |
| Roll Diameter | 127mm (5") user configurable upto 203mm (7") |
| Ribbon Length | 140m (5500") |
| Indexing | Black bar, notch and gap |
| Supported Bar Codes | UPC, EAN, EAN128, Code39, Plessey, MSI/MSI1, Code 16k, Code128, Codabar, MaxiCode, PDF 417, Code93, I2 of 5, more |
| Fonts | |
| Bitmapped | 7 styles with upto 10x10 magnification, variable boldness and spacing (all models) |
| AGFA Fonts | Sans-serif font in 7pt, upto 4x4 magnification, variable boldness and spacing (all models) |
| Scalable Smooth Fonts | 3 ultra font styles for smooth characters any size and boldness (all models) |
| Rotations | 360° in 90° increments |
| Graphics | |
| Features | Foreground and background bitmapped graphics, sizeable graphics window (all models) |
| Format | PCX, BMP |
| Memory | |
| RAM | 2MB |
| Flash | 512KB Flash, +2MB and 4MB options (all models) |
| Communications | |
| Standard | Serial and parallel |
| Ethernet | Internal Ethernet |
| Electrical | 100, 115, or 230 VAC, 50/60Hz |
| Environmental | |
| Operating | 41°F to 104°F (5°C to 40°C) |
| Storage | -4°F to 122°F (-20°C to 50°C), 25-85% non condensing RH |
| Dimensions H x W x D | 177.8mm x 177.8mm x 254mm 7" x 7" x 10" |
| Weight | 3.5lb (1.59kg) |
| Accessories | |
| Supplied | Quick Start Guide, power supply, CD including: Windows® drivers, programmers guide, label design software |
| Optional | Ethernet connectivity, communications cables, annual service contracts, cutter, dispenser, real time clock |
| Printhead Life | 2 Million" (50km) |

All manufacturers trademarks acknowledged. Specifications subject to change without notice. Issue 1 - 2006