



**Maxatec**  
barcode printers

## EZ-LP™

### Desktop Label Printer

Keep your code. Change your printer.™

Change is good... when it's easy, better, and costs less.

The **Cognitive TPG EZ-LP** desktop printer is your alternative to more expensive legacy printers, providing a better value with drop-in compatibility. The **EZ-LP** is a 4" wide direct thermal printer that comes with a durable print mechanism, extensive flash memory, 5" media roll capacity and multiple communication interface options and programming emulations. The **EZ-LP** is ideal for a wide range of applications, including work-in-process (WIP), logistics and retail.

The best choice to refresh legacy ZPL™ and EPL™ desktop applications

- Robust ZcPL and EcPL emulations
- Industry standard communication interfaces (serial, parallel, USB, and Ethernet)
- Only standard USB-A (host) port in its class
- Rugged field proven mechanical design
- 4" model (4.25" media width)
- 203 dpi (8 dots/mm) DT print mode



**Maxatec**  
[www.maxatec-europe.com](http://www.maxatec-europe.com)

Technical Specifications		
Print Method	Direct Thermal	
Width (max)	4.1"/104 mm	
Length (max)	322" (8179 mm) at 203 dpi	
Speed (max)	5 ips (127 mm/sec)	
Resolution	203 dpi (8 dpmm)	
<b>MEDIA</b>		
Width	2" - 4.25" (50 - 108 mm)	
Roll Diameter	5.0" (127 mm) Indexing Black bar, notch and gap	
BAR CODES	EcPL	Code39, Code39 with check digit, Code93, Code128 Auto A/B/C, Codabar, EAN8, EAN8 with 2/5 digit add-on, EAN13, EAN13 with 2/5 digit add-on, Interleaved 2 of 5, Postnet, UCC/EAN 128, UPC A, UPC A with 2 digit add-on, UPC E, UPC E with 2/5 digit add-on, Aztec, DataMatrix, MaxiCode, PDF417
	ZcPL	Code 11, Interleaved 2 of 5, Code 39, Planet Code, PDF417, EAN-8, UPC-E, Code 93, Code 128 (Subsets A,B,and C), UPS MaxiCode, EAN-13, Micro-PDF417, Industrial 2 of 5, Standard 2 of 5, ANSI Codabar, LOGMARS, MSI, Aztec, Plessey, QR Code, RSS, UPC/EAN Extensions, UPC-A, Data Matrix, Bar Code Field Default, POSTNET
FONTS	EcPL	5 bitmapped fonts, up to 8x magnification
	ZcPL	15 bitmapped fonts, one scaleable font
GRAPHICS	Ability to upload and recall. PCX and BMP formats	
MEMORY	RAM 8 MB, Flash - 4 MB	

COMMUNICATIONS	Standard Optional	Serial (DB9) and USB (A&B) Serial (DB9)/Parallel (Centronics) and USB (A&B) Ethernet (internal) and USB (A&B)
ELECTRICAL	Auto-ranging 100-240 VAC, 50-60 HZ, 24VDC output	
ENVIRONMENTAL	Operating	41°F to 104°F (5°C to 40°C)
DIMENSIONS	6.85" (174mm) W x 6.9" (175mm) H x 9.7" (246mm) D	
WEIGHT	3.9 lbs (1.77kg)	
ACCESSORIES	Standard	QuickStart Guide, power supply and cord, user guide, Cognitive Administrative Utility and Window's driver
	Optional	Parallel port, communications cables, label (peeler) dispenser, Ethernet, real- time clock
WARRANTY	Printer	12 months from date of purchase (requires registration and excludes printhead)
PROGRAMMING LANGUAGE	EcPL and ZcPL language emulation	

Issue 1 - 2009

All manufacturers trademarks acknowledged. Specifications subject to change without notice.