

Maxatec

Maxa Technologies Ltd, Atlantic Street, Altrincham, Cheshire,
WA14 5QJ, United Kingdom, Tel: +44 (0) 161 942 7850
Fax: +44 (0) 161 927 7664, Web: www.maxatec-europe.com
Email: info@maxatec-europe.com

POWERFUL AND EASY TO USE, 2 INCH PORTABLE PRINTER

LK-P11

- Compact and rugged design
- IP42, IP54(with optional case) Certified : protection against dust and water
- Large capacity of paper roll up to 56mm (OD)
- Adjustable paper width from 25.4 to 58mm
- Flexible connectivity including RS-232C, USB, Bluetooth or Wi-Fi(802.11b/g)
- Prints at 80mm per second
- Fast AC charger and long life battery : 2.5Hrs charging time, 20Hrs stand-by
- Optional accessories : leather case, shoulder strap, cradle and vehicle charger(12/24V)



● SPECIFICATION

PRINT METHOD		Direct Thermal
PRINTING SPEED		80mm/sec
DOT DENSITY		203 DPI
DOT PITCH		8dots/mm, 0.125 pitch
EFFECTIVE PRINTING WIDTH		48mm, 384dots/line
PAPER	TYPE	Thermal paper / Label
	WIDTH	25.4mm ~ 58mm
	THICKNESS	0.06mm ~ 0.16mm
	ROLL DIAMETER	Max. Ø 56.0mm
	ROLL CORE INNER DIAMETER	12.5mm ± 0.5mm
RELIABILITY	TPH LIFE	50km
	PULSE ACTIVATION	50,000,000pulse or more
FONTS and GRAPHICS	STANDATD FONTS	Seven residnet fonts 12-48 pt.
	OPTIONAL	International Character Sets
	GRAPHICS, LINE AND BOX DRAWING	PCX and Bitmap
BARCODE	EAN-8, EAN-13, Code 39, ITF, UPC-A, UPC-E, Codabar, Code 93, Code 128, PDF 417(2D), QR Code(2D), Maxicode(2D)	
EMULATION	ESC/POS Command compatible	

DRIVER	Window Printer Driver(7, XP, 2000, 2003, VISTA, 32 & 64bit), Windows (CE 4.2 & 5.0 / Mobile 5.0), Linux Printer Driver Symbian, Blackberry	
SENSOR	Paper end / Black mark / Gap / Cover open sensors	
INTERFACE	STANDARD	Serial(RS-232C), USB
	OPTION	Bluetooth class 2, Wi-Fi (802.11b/g)
BATTERY CHARGER	External Charger (Output 8.4VDC/0.8A)	
BATTERY	7.4V 2200mAh Li-ion, 2.5Hrs Charging Time 500 Cycles Rechargeable	
DIMENSION	WxDxH (mm)	104×154×74
	W"xD"xH" (inch)	4.0×6.0×2.9
WEIGHT	490g	
TEMPERATURE	OPERATION	-10 ~ 50°C
	STORAGE	-20 ~ 60°C
HUMIDITY	OPERATION	35 ~ 80 %
	STORAGE	10 ~ 90 %

